

4 qts = 0.95 A

CAPACITIES

1 gal = 3.8 A

Year	Model	Engine Displacement Liters (cc)	Engine ID/VIN	Engine Oil with Filter (qts.)	Automatic Transmission (pts.)	Rear Drive Axle (pts.)	Fuel Tank (gal.)	Cooling System (qts.)
1988	Town car	5.0 (4943)	F	5.0	24.6	3.8	22.1	14.1
	Mark VII	5.0 HO (4943)	E	5.0	24.6	3.8	22.3	14.1
	Continental	3.8 (3802)	4	4.5	26.2	①	18.6	11.1
1989	Town car	5.0 (4943)	F	5.0	24.6	3.8	22.3	14.1
	Mark VII	5.0 HO (4943)	E	5.0	24.6	3.8	22.1	14.1
	Continental	3.8 (3802)	4	4.5	26.2	①	18.6	12.1
1990	Town car	5.0 (4943)	F	5.0	24.6	3.8	18.0	14.1
	Mark VII	5.0 HO (4943)	E	5.0	24.6	3.8	20.0	14.1
	Continental	3.8 (3802)	4	4.5	25.6	①	18.6	12.1
1991	Town car	4.6 (4593)	W	5.0	24.6	3.8	20.0	14.1
	Mark VII	5.0 HO (4943)	E	5.0	24.6	3.8	20.0	14.1
	Continental	3.8 (3802)	4	4.5	25.6	①	18.6	12.1
1992	Town car	4.6 (4593)	W	5.0	24.6	3.8	20.0	14.1
	Mark VII	5.0 HO (4943)	E	5.0	24.6	3.8	20.0	14.1
	Continental	3.8 (3802)	4	4.5	25.6	①	18.6	12.1
1993	Town car	4.6 (4593)	W	5.0	24.6	4.1	20.0	14.1
	Mark VIII	4.6 (4593)	V	6	24.6	3.0	18.0	14.1
	Continental	3.8 (3802)	4	4.5	25.6	①	18.4	11.1
1994	Town car	4.6 (4593)	W	5.0	24.6	4.1	20.0	14.1
	Mark VIII	4.6 (4593)	V	6	25	3.0	18.0	16.0
	Continental	3.8 (3802)	4	4.5	27.4 ③	①	18.4	12.1
1995	Town car	4.6 (4593)	W	5.0	24.6	4.1	20.0	14.1
	Mark VIII	4.6 (4593)	V	6	25	3.0	18.0	16
	Continental	4.6 (4593)	V	6	27.4 ③	①	18.4	14.3
1996	Town car	4.6 (4593)	W	5.0	27.2	②	20.0	14.1
	Mark VIII	4.6 (4593)	V	6	25.6	3.0	18.0	16.0
	Continental	4.6 (4593)	V	6	27.4 ③	3.0	17.8	14.3
1997	Town car	4.6 (4593)	W	5.0	27.2	②	20.0	14.1
	Mark VIII	4.6 (4593)	V	6	25.6	3.0	18.0	16.0
	Continental	4.6 (4593)	V	6	27.4 ③	3.0	17.8	14.3
1998	Town car	4.6 (4593)	W	5.0	27.2	②	20.0	14.1
	Mark VIII	4.6 (4593)	V	6	25.6	3.0	18.0	16.0
	Continental	4.6 (4593)	V	6	27.4 ③	3.0	17.8	14.3
1999	Town car	4.6 (4593)	W	5.0	27.2	②	20.0	14.1
	Continental	4.6 (4593)	V	6	27.4 ③	3.0	17.8	14.3
2000	Town car	4.6 (4593)	W	5.0	27.2	②	20.0	14.1
	Continental	4.6 (4593)	V	6	27.4 ③	3.0	17.8	14.3

NOTE: All capacities are approximate. Add fluid gradually and ensure a proper fluid level is obtained.

- ① Included in the transaxle capacity
- ② 7.50" axle: 3.0 pts.  
8.80" axle: 3.25 pts.
- ③ Includes torque converter.