

LUBRICATION (Continued)

3.0L/3.2L SHO Engines

7,500 MILES (12,000 Kilometers)

POWER STEERING PUMP DIPSTICK  
FLUID SHOULD BE IN THE FULL COLD OR FULL HOT RANGE DEPENDING ON TEMPERATURE

ENGINE OIL DRAIN PLUG LOCATED IN OIL PAN

MANUAL TRANSAXLE FILL PLUG  
FILL TO BOTTOM OF FILLER HOLE WITH VEHICLE LEVEL

BRAKE MASTER CYLINDER

AIR FILTER FA-1042  
REPLACE ELEMENT AT RECOMMENDED INTERVAL

BELTS  
CHECK BELTS AT RECOMMENDED INTERVAL


ENGINE COOLANT RESERVOIR (3.2L ONLY)

RADIATOR CAP

SHO 24 VALVE DOHC

ENGINE OIL FILLER CAP

WINDSHIELD WASHER RESERVOIR



BATTERY  
BXT-34


ENGINE COOLANT RESERVOIR (3.0L ONLY)

"CHECK ENGINE OIL" ENGINE OIL LEVEL DIPSTICK

KEEP THE OIL IN THIS RANGE



OIL LEVEL WILL NORMALLY BE IN THIS RANGE AFTER AN OIL CHANGE



OIL FILTER FL400-A  
COAT GASKET WITH ENGINE OIL. REPLACE FILTER AT RECOMMENDED INTERVAL.

Y4243-A