

REMOVAL AND INSTALLATION (Continued)

Roof Luggage Carrier


Rails and Slats

Removal

1. Lower vehicle headliner. Refer to Section 01-05.
2. For rails, remove eight retaining nuts per side.
3. For slats, drill out five rivets at each slat.

Installation

1. For slats, position on vehicle roof after applying sealer around rivet holes. Rivet into place.
2. For rails, position on vehicle roof after applying sealer around holes. Install eight nut and washer assemblies. Tighten to 1.4-2.3 N-m (13-20 lb-in).
3. Install headliner. Refer to Section 01-05.



Mouldings, Exterior

Before removing the exterior mouldings, it should be determined by the type of retainer used, whether a respective door, quarter or luggage compartment trim panel must first be removed to provide access. If a weld stud is distorted or broken off, it should be replaced with an oval head blind rivet (Part No. 383229-S). Refer to the following illustrations to remove and install exterior mouldings.

1. Remove the trim panel or door, quarter or luggage compartment trim panel as required to provide access to the moulding.
2. Remove the moulding by pulling it away from the surface. If the moulding is secured with a retainer, remove the retainer first.
3. If the moulding is secured with a retainer, remove the retainer first.
4. If the moulding is secured with a retainer, remove the retainer first.
5. If the moulding is secured with a retainer, remove the retainer first.
6. If the moulding is secured with a retainer, remove the retainer first.
7. If the moulding is secured with a retainer, remove the retainer first.
8. If the moulding is secured with a retainer, remove the retainer first.
9. If the moulding is secured with a retainer, remove the retainer first.
10. If the moulding is secured with a retainer, remove the retainer first.

1. Remove the trim panel or door, quarter or luggage compartment trim panel as required to provide access to the moulding.
2. Remove the moulding by pulling it away from the surface. If the moulding is secured with a retainer, remove the retainer first.
3. If the moulding is secured with a retainer, remove the retainer first.
4. If the moulding is secured with a retainer, remove the retainer first.
5. If the moulding is secured with a retainer, remove the retainer first.
6. If the moulding is secured with a retainer, remove the retainer first.
7. If the moulding is secured with a retainer, remove the retainer first.
8. If the moulding is secured with a retainer, remove the retainer first.
9. If the moulding is secured with a retainer, remove the retainer first.
10. If the moulding is secured with a retainer, remove the retainer first.