

SPECIFICATIONS

TORQUE SPECIFICATIONS

Description	N-m	Lb-Ft
Body Mount Retaining Bolts	75-102	55-75
Body Mount to Subframe Bolts	8-11	6-8
Transaxle Mount-to-Subframe Bolts (LH)	81-116	60-85
Front Engine Mount-to-Subframe Bolts (RH)	75-102	55-75
Rear Engine Mount-to-Subframe Bolts (RH)	75-102	55-70
Stabilizer Link-to-Stabilizer Bar Nuts	47-65	35-47
Gear-to-Crossmember Nuts	115-135	85-99

SPECIAL SERVICE TOOLS

Tool Number	Description
D88L-6000-A	Three Bar Engine Support



1. Remove the lower control arm bolts from the subframe.

2. Remove the lower control arm nuts from the subframe.

3. Remove the lower control arm bolts from the subframe.

4. Remove the lower control arm nuts from the subframe.

5. Remove the lower control arm bolts from the subframe.

6. Remove the lower control arm nuts from the subframe.

7. Remove the lower control arm bolts from the subframe.

8. Remove the lower control arm nuts from the subframe.

9. Remove the lower control arm bolts from the subframe.

10. Remove the lower control arm nuts from the subframe.

1. Remove the lower control arm bolts from the subframe.

2. Remove the lower control arm nuts from the subframe.

3. Remove the lower control arm bolts from the subframe.

4. Remove the lower control arm nuts from the subframe.

5. Remove the lower control arm bolts from the subframe.

6. Remove the lower control arm nuts from the subframe.

7. Remove the lower control arm bolts from the subframe.

8. Remove the lower control arm nuts from the subframe.

9. Remove the lower control arm bolts from the subframe.

10. Remove the lower control arm nuts from the subframe.