

SECTION 03-04B Fuel Charging and Controls—3.0L/3.2L SHO

SUBJECT	PAGE	SUBJECT	PAGE
CLEANING AND INSPECTION		REMOVAL AND INSTALLATION	
Air Cleaner	03-04B-13	Air Intake Throttle Body	03-04B-8
Preferred Cleaning Procedure	03-04B-12	Fuel Charging Assembly	03-04B-4
COMPONENTS		Fuel Injection Pulse Dampener	03-04B-12
Fuel Injection Pulse Dampener	03-04B-3	Fuel Injector(s)	03-04B-11
Fuel Injection Supply Manifold Assembly	03-04B-4	Fuel Pressure Regulator	03-04B-11
Fuel Injectors	03-04B-3	Fuel Rail Assembly	03-04B-10
Fuel Pressure Regulator	03-04B-3	Idle Air Control (IAC) Valve Assembly	03-04B-9
Throttle Body Assembly	03-04B-4	Intake Manifold and Throttle Body	03-04B-8
DESCRIPTION	03-04B-1	Throttle Position Sensor	03-04B-9
OPERATION		SPECIAL SERVICE TOOLS	03-04B-13
Air Intake Manifold	03-04B-2	SPECIFICATIONS	03-04B-13
PARTS CROSS-REFERENCE	03-04B-13	VEHICLE APPLICATION	03-04B-1

VEHICLE APPLICATION

Taurus SHO.

DESCRIPTION

The sequential multiport fuel injection (SFI) system is classified as a multi-point, pulse time, speed density control, fuel injection system. Fuel is metered into each intake port in sequence with the engine firing order in accordance with engine demand through six fuel injectors (9F593) mounted on a tuned intake manifold.

WARNING: DO NOT SMOKE, CARRY LIGHTED TOBACCO, OR OPEN FLAME OF ANY TYPE WHEN WORKING ON OR NEAR ANY FUEL-RELATED COMPONENT. HIGHLY FLAMMABLE MIXTURES ARE ALWAYS PRESENT AND MAY BE IGNITED, RESULTING IN POSSIBLE PERSONAL INJURY.

An on-board vehicle powertrain control module (PCM) (12A650) accepts inputs from various engine sensors to compute the fuel flow rate necessary to maintain a prescribed air / fuel ratio throughout the entire engine operational range. The PCM then outputs a command to the fuel injectors to meter the appropriate quantity of fuel.

The EEC-IV engine control system also determines and compensates for the age of the vehicle and its uniqueness. The system will automatically sense and compensate for changes in altitude (i.e. from sea level to mountains) and will also permit push-starting the vehicle if necessary (manual transaxle only).

All engines use a closed-type positive crankcase ventilation (PCV) system and an exhaust emission system to control engine emissions within Government specifications.

To maintain the required exhaust emission levels, the fuel metering system must be kept in good operating condition and adjusted to specifications listed in the applicable Section of the Powertrain Control/Emissions Diagnosis Manual¹, the applicable Section of this Group, or on the Vehicle Emission Control Information (VECI) decal.

Additional engine performance checks are required to keep the exhaust emissions at the specified minimum pollutant level. Refer to the Pre-Delivery manual, Section 00-03, for these performance checks and recommended intervals.

Always refer to the Master Parts List for parts usage and interchangeability before replacing a throttle body (9E926) or a component part of a throttle body.

¹ Can be purchased as a separate item.