

REMOVAL AND INSTALLATION (Continued)

(Continued) REMOVAL AND INSTALLATION

| Item | Part Number | Description |
|------|-------------|--|
| 1A | N606688-S2 | Screw and Washer Assy |
| 2 | 9E857 | Canister and Bracket Assy |
| 3 | 9K313 | Fuel Vapor Front Hose |
| 4 | — | Radiator Support |
| 5 | 9C987 | Hose and Valve Assy |
| A | | Tighten to 21.2-28.8 N·m (15-21 Lb-Ft) |

SPECIAL SERVICE TOOLS

| ROTUNDA EQUIPMENT | |
|-------------------|------------------------------------|
| Model | Description |
| 021-00014 | Rotunda Vacuum and Pressure Tester |

| Tool Number | Description |
|-------------|-----------------------------------|
| SFT-265 | Stant Fuel System Pressure Tester |

| Item | Part Number | Description |
|------|-------------|--|
| 1A | N606688-S2 | Screw and Washer Assy |
| 2 | 9E857 | Canister and Bracket Assy |
| 3 | 9K313 | Fuel Vapor Front Hose |
| 4 | — | Radiator Support |
| 5 | 9C987 | Hose and Valve Assy |
| A | | Tighten to 21.2-28.8 N·m (15-21 Lb-Ft) |

| Item | Part Number | Description |
|------|-------------|--|
| 1A | N606688-S2 | Screw and Washer Assy |
| 2 | 9E857 | Canister and Bracket Assy |
| 3 | 9K313 | Fuel Vapor Front Hose |
| 4 | — | Radiator Support |
| 5 | 9C987 | Hose and Valve Assy |
| A | | Tighten to 21.2-28.8 N·m (15-21 Lb-Ft) |

