

# SECTION 04-02 Suspension and Wheel Ends, Rear

SUBJECT	PAGE	SUBJECT	PAGE
<b>DESCRIPTION AND OPERATION</b>		<b>REMOVAL AND INSTALLATION (Cont'd.)</b>	
Component Replacement .....	04-02-4	Shock Absorber Strut, Upper Mount and Spring .....	04-02-13
Components .....	04-02-3	Springs .....	04-02-25
Sedan .....	04-02-1	Stabilizer Bar, Insulators and Link Assembly .....	04-02-16
Station Wagon .....	04-02-2	Suspension Arm, Lower .....	04-02-21
Wheel Assembly .....	04-02-8	Suspension Arms, Upper .....	04-02-19
<b>REMOVAL AND INSTALLATION</b>		Tension Strut .....	04-02-21
Anti-Lock Sensor Ring .....	04-02-30	<b>SPECIAL SERVICE TOOLS</b> .....	04-02-32
Bearing and Hub Assembly, Disc Brakes .....	04-02-29	<b>SPECIFICATIONS</b> .....	04-02-31
Bearing and Hub Assembly, Drum Brakes .....	04-02-29	<b>VEHICLE APPLICATION</b> .....	04-02-1
Control Arm .....	04-02-28		
Shock Absorber .....	04-02-12		

## VEHICLE APPLICATION

Taurus/Sable.

## DESCRIPTION AND OPERATION

### Sedan

These vehicles use a MacPherson strut independent rear suspension. Each side consists of an upper mount and washers, a shock absorber strut assembly, two parallel control arms per side, tension strut, cast spindle and shock strut mounted stabilizer bar.