
LOCATION (Continued)

Wagon With Auxiliary Seat, U.S. With Auxiliary Seat, Canada—All

Standard on Canadian Wagon models and on U.S. Wagon models with the auxiliary (third) seat, tether attachments have been provided on the auxiliary seat center support bracket for attaching rear (second) seat tether restraints only.



REMOVAL AND INSTALLATION

Lap/Shoulder Safety Belt Retractor Assembly, Front

NOTE: Seat Belt Bolt Bit T77L-2100-A or equivalent should be used for safety belt bolt removal and installation on front outboard belts. A metric socket is necessary to remove or install inboard buckles and center passenger belt anchors.

Removal

- 1. Remove D-ring cover.
- 2. Insert bolt bit and remove belt bolt.
- 3. Remove B-pillar upper trim panel.
- 4. Remove scuff plate / center pillar trim panel retaining screws and panel.
- 5. Remove safety belt through slot in upper center trim panel.
- Remove safety belt anchor plate-to-sill bolt and rubber washer.
- 7. Remove safety belt retractor bolt.
- Remove web guide retaining screw and slide guide rearward to remove from B-pillar.
- Remove outboard safety belt assembly from vehicle.
- Remove nut/bolt from inboard buckle assembly.
 On LH side, disconnect warning chime wire and pry locator off the seat.
- 11. Pull buckle upward to remove from seat.

Installation

- 1. To install, reverse Removal procedure. Be sure to position belts as shown.
- Tighten all attaching bolts to 30-40 N·m (23-29 lb-ft). Cycle system several times to ensure proper operation of retractor. Make sure belt is not twisted.