

SECTION 03-01B Engine, 3.0L/3.2L SHO

SUBJECT	PAGE
DESCRIPTION	
Engine Code Information Label.....	03-01B-2
Induction System	03-01B-4
Lubrication System	03-01B-5
Positive Crankcase Ventilation (PCV)	03-01B-5
Vehicle Emission Control Information (VECI) Label	03-01B-2
DISASSEMBLY AND ASSEMBLY	
Cylinder Head.....	03-01B-43
Engine.....	03-01B-37
Subassemblies.....	03-01B-41
PARTS CROSS-REFERENCE	03-01B-51
REMOVAL AND INSTALLATION	
Camshaft	03-01B-33
Camshaft Seal(s)	03-01B-36
Connecting Rod Bearings	03-01B-33
Crankshaft/Damper/Front Oil Seal	03-01B-17
Cylinder Head Cover.....	03-01B-19
Cylinder Heads.....	03-01B-21

SUBJECT	PAGE
REMOVAL AND INSTALLATION (Cont'd.)	
Engine.....	03-01B-6
Engine Damper, LH	03-01B-8
Engine Damper, RH.....	03-01B-8
Exhaust Manifold, LH.....	03-01B-28
Exhaust Manifold, RH.....	03-01B-28
Intake Manifold	03-01B-20
Main Bearing Inserts.....	03-01B-29
Oil Pan and Oil Pump	03-01B-26
Pistons and Connecting Rods	03-01B-24
Sensors.....	03-01B-27
Thermostat	03-01B-21
Throttle Body	03-01B-9
Timing Belt	03-01B-10
Water Pump	03-01B-19
SPECIAL SERVICE TOOLS	03-01B-50
SPECIFICATIONS	03-01B-45
VEHICLE APPLICATION	03-01B-1

VEHICLE APPLICATION

Taurus with 3.0L / 3.2L SHO engine.

DESCRIPTION

The 3.0L / 3.2L SHO is a high performance V-6 engine with DOHC (double overhead camshafts), four valves per cylinder, and sequential multiport fuel injection (SFI). The engine has aluminum cylinder heads, 24 valves, shim set bucket tappets and a cast-iron, 60 degree V-block.

CAUTION: This engine has aluminum cylinder heads and requires a special corrosion inhibiting coolant to avoid cooling system damage. Refer to Section 03-03 for the coolant specifications.

The left and right bank intake camshafts are driven by a timing belt. Then, the intake camshafts drive the exhaust camshafts on the rear of the engine through timing chains.

The ignition system is distributorless, with a three pack coil assembly. The ignition control module (ICM) 12A297 is mounted on the upper intake connector tube. The high-energy ignition system is required for fast-burn combustion. The spark plugs are 14mm with a 0.044 inch gap and are centrally located in the combustion chambers.

A unique air intake system utilizes a secondary intake port along with a primary intake port. The secondary port is opened and closed by a vacuum-operated intake air control valve, thus improving low and mid-range torque and fuel efficiency.